

fermacell™ Fine Surface Treatment

For fermacell® gypsum fibreboards

fermacell™ Fine Surface Treatment (FST) is a ready-to-use dispersion material for the universal fine filling of interior wall and ceiling areas. It is also ideal for achieving quality grades Q3 and Q4 if the finish must be to a superior standard.

Installation

The substrate must be clean, sound and dry. fermacell™ FST must be applied at air and substrate temperatures of not less than +5 °C (max. layer thickness ≤0.5 mm per application). We recommend using a fermacell™ spatula to apply the product. The spatula should be dried thoroughly after cleaning to prevent rusting. When sanding use a grit size of 100 – 120. Safety glasses / goggles and a mask must be worn during sanding operations. Remove dust from sanded areas before applying wall coverings or paint.

Drying time: dependent on the substrate, layer thickness, temperature and humidity.



**Fermacell UK,
Division of James Hardie Building
Products Ltd**
7 The Priory
Old London Rd
Sutton Coldfield B75 5SH

Technical support

Tel 0121 311 3480
E-mail info@jameshardie.co.uk
Web www.fermacell.co.uk

Properties

- **Speed & economy**
 - Ready to use
 - Simply close container after use, ready for the next application
- **Easy to apply**
 - Creamy consistency and a smooth filler
 - Long open time, easy to sand smooth
 - fermacell™ FST LS is ideal for machine application
- **High-quality finish**
 - Very smooth surface
 - Excellent filling power and high bond strength
 - Open to diffusion
 - Not susceptible to crazing
- **Universal areas of application**
 - The formulation is specially designed for application to fermacell® gypsum fibreboard surfaces, but is also eminently suitable as a surface treatment on other sound substrates, such as gypsum plasterboard, concrete, masonry etc.
- **Emission-free, solvent-free and plasticizer-free**

Material properties	
Consumption	approx. 0.2 l/ m²
Volume weight	1.2 kg/litre
Adhesion	approx. 1.0 N/mm²
Filling power	High
Cleaning	Clean with water
Drying time	approx. 2 – 3 h/mm
Storage	12 months, cool and protected from frost
Colour	White
Container sizes	3 l, 10 l

Distributor information		
	3 l tub	10 l tub
Article number	79007	79002
EAN	4007548005937	4007548002158
Customs tariff no.	32141090	32141090
Quantity / Pallet	96	44
Weight / Pallet	385 kg	575 kg

Additional information

If wet screed / asphalt flooring is being installed, the FST must not be applied until the screed work has been completed.